

562584

Development of a PMAD System for Flywheel Based Energy Storage System

This is a preprint or reprint of a paper intended for presentation at a conference. Because changes may be made before formal publication, this is made available with the understanding that it will not be cited or reproduced without the permission of the author.

Glenn Research Center



at Lewis Field


What We Will Discuss:

- Flywheel Energy Storage System (FESS) program objective
- Benefits of Flywheels for International Space Station (ISS)
- FESS Development Team
- FESS Electrical Requirements
- FESS Electrical Architecture
- Electrical Subsystem Functionality
- Conclusion




Program Objective

ISS Power System Channel Baseline



ISS Power System Channel with Flywheels



- To demonstrate flywheel technologies operating together as a system and having improved performance characteristics over batteries in a low earth orbit energy storage application (ISS).

Glenn Research Center



at Lewis Field

Benefits of Flywheels for ISS

- 15 year life vs. 5 year design life for NiH2 batteries
- Energy efficiency: 84% roundtrip vs. 67% (spec'd) for BCDU/battery combination
- Cost: projected to be \$100's M for fully populated station over life

Glenn Research Center

at Lewis Field



FESS Development Activities

- University of Texas, Center for Electro Mechanics – Flywheel Module design and development
 - Rotor design
 - Magnetic Bearing system design (including control software)
 - Motor/Generator design
 - Mechanical Bearing design
 - Module Integration
- TRW - Electronics design and development
 - Motor drive electronics
 - Magnetic bearing drive electronics
 - Magnetic Bearing and Motor Drive DSP development
 - System Controller design
 - Electronics Integration

Glenn Research Center



at Lewis Field

FESS Development Activities (cont.)

- GRC Development Unit testing
 - Motor control algorithm design
 - Magnetic Bearing sensor evaluation
 - FESS/ISS EPS integration testing
 - Advanced concepts development
 - Combined power and torque control
 - Passive Magnetic Bearings
 - Alternate Magnetic Bearing Controls

Glenn Research Center

at Lewis Field



FESS Electrical Requirements


- 6.6 kW input or output power for charge or discharge
- 5.25 kW-hr energy storage from full speed to minimum speed
 - Enough for 2 contingency orbits of operation
- 130 to 173 VDC primary bus voltage
- 84% round-trip energy efficiency, including fixed losses and power electronics
- Autonomous operation and transition from charge to discharge
- Parallels with ISS NiH2 batteries and Battery Charge/Discharge

Glenn Research Center



at Lewis Field

FESS Electrical Architecture





Glenn Research Center

at Lewis Field



FESS Master Control Subsystem




- Provides communication to ISS EPS via MIL Std 1553
- Controls FESS operations and sequencing
- Collects telemetry to monitor state-of-health and to transmit to ground
- Makes flywheel “look like a battery”

Glenn Research Center



at Lewis Field

FESS Motor Drive Subsystem




- Motor Drive hardware is common Power Electronics Building Block converter
- Inverter operates as buck converter during charge, boost converter during discharge
- 4 Pole Permanent Magnet Synchronous Motor selected
- Status: Bidirectional power control of charge current and discharge voltage demonstrated

Glenn Research Center


at Lewis Field



FESS Magnetic Bearing Subsystem



- Magnetic Bearing Drive hardware is common Power Electronics Building Block converter
- Control designed to minimize input current/energy
- Control designed to filter imbalance effects
 - Operates on disturbances
- Status: Control of levitation demonstrated to 60,000 RPM





Glenn Research Center



at Lewis Field

FESS Power Distribution Subsystem



- Supplies power to control DSPs and magnetic bearing PWMs
- Uses either ISS primary or energy from flywheels as a source
- Multiple sources provide fault tolerance for communication and wheel levitation
- Fault Isolator protects against shorts on the power bus

Glenn Research Center

at Lewis Field



Conclusion

- FESS will demonstrate some of the benefits of flywheel technology for LEO energy storage
- Development team is in place
- Functionality of motor drive and magnetic bearing subsystems has been demonstrated
- Performance characterization and improvement is on-going

Glenn Research Center

at Lewis Field

